

Flow Control & Needle Valves

Connections: 1/8 - 11/2 BSP

Inline needle valves with micrometer scale



- ✓ Ex Stock
- UK Assembly
- © Please Call Sales Office

DV Series, Double Acting Flow Control & Shut-off (Bi-directional)

Part Number		BSP	BAR	LPM MAX	
DV-G18	✓	1/8	350	10	
DV-G14	✓	1/4	350	50	
DV-G38	✓	3/8	350	75	
DV-G12	✓	1/2	350	140	
DV-G34	✓	3/4	350	175	
DV-G100	✓	1	350	350	
DV-G114	✓	1 1/4	350	350	
DV-G112	✓	1 1/2	350	350	

Technical Data Materials

DV/DRV: Zinc-Plated Carbon Steel, Nitrile seals

FT: Nickel plated brass (stainless steel where stated), Nitrile seals

Operating Pressure DV/DRV: 350 BAR

FT: 210 BAR

Operating Temperature

-20°C - to +100°C

Special Requests

For assistance, contact our technical office or your local Camozzi distributor.



- ✓ Ex Stock
- UK Assembly
- © Please Call Sales Office

DRV Series, Single Acting Flow Control, Free reverse Flow (Uni-directional)

Part Number		BSP	BAR	LPM MAX	
DRV-G18	✓	1/8	350	10	
DRV-G14	✓	1/4	350	50	
DRV-G38	✓	3/8	350	75	
DRV-G12	✓	1/2	350	140	
DRV-G34	✓	3/4	350	175	
DRV-G100	✓	1	350	350	
DRV-G114	✓	1 1/4	350	350	
DRV-G112	✓	1 1/2	350	350	
DRV-G200	✓	2	350	350	