



The undersigned, representative of the following manufacturer

**Camozzi Automation S.p.A.**

Via Eritrea, 20/I  
25126 Brescia - Italy  
Tel: +39 030 37921  
Fax: +39 030 2400464  
E-mail: [info@camozzi.com](mailto:info@camozzi.com)  
<http://www.camozzi.com>

herewith declares that the products:

**Solenoid valves Series PL**

*assembled with the solenoid versions reported on the last page*

The object of the declaration described above is in conformity with the relevant Union harmonisation legislation::

**2014/30/EU**

DIRECTIVE 2014/30/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility

and that all the standards and/or technical specifications indicated on page 2 are applied.

This declaration of conformity is issued under the sole responsibility of the manufacturer

Brescia, Italia 22/10/2019

Camozzi Automation S.p.A.  
Product Certification Manager  
Guerrini Fabrizio



Reference relative to the standards and/or technical specifications, or parts of them, used for the present declaration of compliance

Reference Number	Date of issue	Title
EN 61000-6-4	2007 + A1 : 2011	Emission for residential, commercial and light-industrial environments
EN 61000-6-2	2005	Immunity for industrial environments
EN 55014-1	2006	Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission

Code example:

PL	0	00	-	3	0	3	-	PL	2	3			
<b>PL SERIES</b>													
<b>0 BODY DESIGN:</b> 0 = single sub-base (M5 only) or interface 1 = single manifold 2 = double sided manifold													
<b>00 NUMBER OF POSITIONS:</b> 00 = interface 01 = single base (M5 only) 02 ÷ 99 = manifold number of positions													
<b>3 NUMBER OF WAYS - FUNCTIONS:</b> 0 = manifold or single base 3 = 3-way NC 5 = 3-way NC electric part revolved by 180°													
<b>0 VALVE PORTS:</b> 0 = interface (for single valve only)													
<b>MANIFOLD PORTS:</b> 2 = M5 side port 3 = ∅ 3 tube side port 4 = ∅ 4 tube side port 6 = M5 rear ports 7 = ∅ 3 tube rear ports 8 = ∅ 4 tube rear ports													
<b>3 NOMINAL DIAMETER:</b> 3 = ∅ 1.5 mm (Pressure 4 ÷ 8 bar) 6 = ∅ 1.5 mm (Pressure 0 ÷ 3.5 bar)													
<b>PL MATERIALS:</b> PL = technopolymer PBT body, FKM poppet seal, other seals in NBR													
<b>2 ELECTRICAL CONNECTION:</b> 2 = industrial standard connection (9.4 mm)													
<b>3 VOLTAGE - POWER CONSUMPTION:</b> 2 = 12 V DC* 2.7W 3 = 24 V DC* 2.7W													
<b>FIXING:</b> = with screws for metal (standard) P = with screws for plastics													
<b>OTHER FEATURES:</b> S = Custom product													
<b>Position reserved for custom products</b> 01 ÷ 99 = number for special application													

\*Voltage tolerance from +10% to -10%