

In-Line Check Valves



FT 260/6 - Ball type closure - Carbon Steel

Thread	PN BAR	Carbon Steel/Buna
1/8	350	FT260/6-G18
1/4	350	FT260/6-G14
3/8	350	FT260/6-G38
1/2	350	FT260/6-G12
3/4	350	FT260/6-G34
1	350	FT260/6-G100

ATR Series - Metal to Metal Seal - Carbon Steel*

Thread	PN BAR	Carbon Steel/Buna
1/8	300	ATR-G18
1/4	300	ATR-G14
3/8	300	ATR-G38
1/2	300	ATR-G12
3/4	300	ATR-G34
1	300	ATR-G100
1 1/4	300	ATR-G114
1 1/2	300	ATR-G112
2	200	ATR-G200

*Standard spring 5psi, for other options contact the sales office

Technical Data

Materials

FT 260/6: Black Carbon Steel
 ATR Series: Yellow Carbon Steel
 FT 2260: Stainless Steel/WITON
 ATR-X: Stainless Steel (316)

Cracking Pressure

FT: 0.35 BAR or 4.5 BAR
 ATR: 0.35/1.5/2.5/4/6 BAR

Operating Temperature

-20°C - to +100°C

Special Requests

For assistance, contact our technical office or your local Camozzi distributor.