

Flexible Nylon Recoils

Tubing to (BS5409)

Applications: TRNR flexible nylon recoils are manufactured from high quality nylon granules and are suitable for use in a wide range of pneumatic applications.

Flexible nylon recoils are fitted with BSPT swivel fittings and anti-kink tube nuts as standard.



Flexible Nylon Tubing - MetricOD	ID	Working	BSPT	Working	
mm	mm	Length metre	Swivel Fitting	Pressure bar	
TRNR-0602	6	4	2.5	1/4	24
TRNR-0605	6	4	5	1/4	24
TRNR-0610	6	4	10	1/4	24
TRNR-0615	6	4	15	1/4	24
TRNR-0802	8	6	2.5	1/4	17
TRNR-0805	8	6	5	1/4	17
TRNR-0810	8	6	10	1/4	17
TRNR-0815	8	6	15	1/4	17
TRNR-1002	10	8	2.5	3/8	14
TRNR-1005	10	8	5	3/8	14
TRNR-1010	10	8	10	3/8	14
TRNR-1015	10	8	15	3/8	14
TRNR-1202	12	9	2.5	3/8	11
TRNR-1205	12	9	5	3/8	11
TRNR-1210	12	9	10	3/8	11
TRNR-1215	12	9	15	3/8	11

Flexible nylon recoils are available without BSPT swivel fittings on request.
Please note: not suitable for constant rotation.

Technical Data

Standard Coil Lengths

See table

Other lengths available on request

Materials

TRNR coils are manufactured from nylon

11 or 12

Operating Temperature

-35°C to +70°C

Brittle temperature: -70°C

Working Pressure

Values stated are based on the short term burst pressure of nylon at 20°C using a 4:1 safety factor.

For data over 20°C, contact our sales office

Chemical Resistance

Resistant to most solvents, alkalis, oils, greases, petroleum products, and dilute acids (mineral and organic).

For further information, contact our sales office

Approvals

Tubing manufactured to BS5409 (1 and 2)

This product range is not suitable for food and drinks applications

Technical Advice

For assistance, contact our technical office or your local Camozzi distributor.